

## HMI with an additional VGA Input

- Combine HMI and Monitor in one machine, saving cost and space
- Support VGA Input
- Come in two size: 7" & 10.2"



Model		P5070VS	P5102VS
Display	Display Type	TFT LCD, 16.7M Colors	
	Display Size	7.0" (16:9)	10.2" (16:9)
	Resolution	800 X 480	800 X 480
	Backlight	LED, 400nits	LED, 350nits
	Backlight Life	30,000 Hrs.	
Touch	Type	4-wire Resistive Film	
Real-time Clock		Built-in	
I/O Port	Serial 1	Connector: D-Sub 9-Pin COM1: RS-232 (TXD, RXD) COM2: RS-422/485 COM3: RS-485	
	Video	Connector: D-Sub 15-Pin VGA Input (Resolution fix in 800X600)	
	LAN	---	---
	USB	USB2.0 Type-A (Host)x1 USB2.0 Type mini-B (Device)x1	
	PLC Extension	HB1 main units + B1 extension modules	
	Termination Switch	Yes (For RS-422/485)	
	Power	Power Input	24Vdc±20% (Isolated Power)
Consumption (@24V)		0.46A	0.48A
Insulation		50MΩ at 500VDC	
Dimension/ Weight	Cut-out (mm)	191.5*137.5	259.5*201.5
	W x H x D (mm)	201.0*147.0*38.1	271.5*213.5*44.6
	Weight (g)	630	1360
Certification		CE	